

- MODELS**
- ATC** - COOLING ONLY
 - ATHC** - HEATING & COOLING
 - ATCR** - COOLING ONLY
with RELIEF COLLAR
 - ATHCR** - HEATING & COOLING
with RELIEF COLLAR

- INSTALLATION**
- LAY-IN T-BAR
 - SURFACE MOUNTED
 - 9/16" NARROW SLOT
 - VECTOR T-BAR

- DUCT CONNECTION DIAMETER**
- | DUCT DIAMETER | DUCT DIAMETER WITH RELIEF COLLAR |
|--------------------------------|----------------------------------|
| <input type="checkbox"/> 6" Ø | <input type="checkbox"/> 6R" Ø |
| <input type="checkbox"/> 8" Ø | <input type="checkbox"/> 8R" Ø |
| <input type="checkbox"/> 10" Ø | <input type="checkbox"/> 10R" Ø |
| <input type="checkbox"/> 12" Ø | <input type="checkbox"/> 12R" Ø |
- (Collar Field Installed)

- DISCHARGE PATTERN**
- 1 WAY
 - 2 WAY (OPPOSITE)
 - 2 WAY (CORNER)
 - 3 WAY
 - 4 WAY
- (BLANK-OFF BAFFLES USED)

- MATERIAL**
- STEEL
 - ALUMINUM
 - 304 STAINLESS STEEL

- FINISH**
- ARCTIC WHITE
 - OPTIONAL ANEMOSTAT COLORS
 - CUSTOM COLOR MATCH
 - SATIN POLISHED FINISH ON EXPOSED SURFACES (STAINLESS STEEL ONLY)
 - MILL FINISH (ALUMINUM ONLY)
 - NATURAL ANODIZED (ALUMINUM ONLY)

- OPTIONS**
- TBF - T-BAR FRAME

