MODEL
- ❑ **DU1** - Attenuator Flanged Discharge
- ❑ **DU2** - Attenuator Slip & Drive Discharge
- ❑ **DU3** - Short DU Flanged Discharge
- ❑ **DU4** - Short DU Slip & Drive Discharge

BOX SIZE
- ❑ A
- ❑ B
- ❑ C
- ❑ D
- ❑ E
- ❑ F

INLET SIZE

HOT INLET	COLD INLET
❑ 5" Ø	❑ 5" Ø
❑ 6" Ø	❑ 6" Ø
❑ 7" Ø	❑ 7" Ø
❑ 8" Ø	❑ 8" Ø
❑ 9" Ø	❑ 9" Ø
❑ 10" Ø	❑ 10" Ø
❑ 12" Ø	❑ 12" Ø
❑ 14" Ø	❑ 14" Ø
❑ 16" Ø	❑ 16" Ø

CONTROL SYSTEM
- ❑ Pneumatic Controls
- ❑ Electronic Analog Controls
- ❑ Direct Digital Controls (DDC)
- ❑ Electric Controls

Control strategies available for all applications

CASING TREATMENTS
- ❑ 1/2" Matte Insulation
- ❑ 1" Matte Insulation
- ❑ 1/2" Foil Faced Insulation
- ❑ 1" Foil Faced Insulation
- ❑ 1" Fibre-Lok Insulation
- ❑ 3/8" Fiber-Less Insulation
- ❑ Dual Wall



REHEAT OPTIONS
- ❑ 1 Row Hot Water Coil
- ❑ 2 Row Hot Water Coil
- ❑ 4 Row Hot Water Coil
- ❑ Electric Coil

- ❑ Right Hand Connection
- ❑ Left Hand Connection

ELECTRIC COILS
- ❑ 120 Volts
- ❑ 277 Volts
- ❑ 208 Volts
- ❑ 480 Volts
- ❑ 240 Volts

- ❑ 1 Phase
- ❑ 3 Phase

- ❑ 1 Step
- ❑ 3 Step
- ❑ 2 Step

- ❑ Door Interlocking Disconnect Switch, Non-Fused
- ❑ Power Fusing
- ❑ Primary Fused Transformer

ACCESSORIES

ACCESS DOORS
- ☑ Bottom

- ❑ Patch Plate
- ❑ Hinged Camlock
- ❑ Double Camlock

CASING OPTIONS
- ❑ Unit Mounting Bracket (shipped loose)
- ❑ Standard Control Enclosure
- ❑ Large Control Enclosure
- ❑ Hinged Front Panel (control enclosure)

ELECTRIC CONTROLS
- ❑ Control Transformer
- ❑ Low Voltage Control Disconnect Switch
- ❑ Low Voltage Fuse & Fuse Block
- ❑ Low Voltage Disconnect Switch
- ❑ Low Voltage Power-Fusing
- ❑ 24 VAC Actuator