

## MINIMUM SECURITY

### Fire Rated Fusible Link DOOR GRILLE with Lattice Plate

#### STANDARD FEATURES

- FACE PLATE: 12 GA C.R.S. Lattice Face Plate and Security Grille - 13/16" square holes on 1" centers FLDL-UL-SG1 - Grille one side FLDL-UL-SG2 - Grille two sides
- LOUVER BLADES: 18 GA C.R.S.
- FASTENERS: #8 x 1" Phillips head screw
- FREE AIR FLOW: 40% free area
- Door Thickness: 1 3/4"

#### FINISH

- STANDARD: White Powder Coat Finish
- OPTIONAL: Consult factory for other finishes

#### OPTIONAL FEATURES

- MATERIAL: #304 or #316 stainless steel, #4 finish (satin), or zinc plated galvanized
- TAMPERPROOF SCREWS: See inside back cover, page i, and consult factory for specific product applications
- WIRE SCREEN: galvanized, aluminum, charcoal aluminum, stainless steel attached or framed

#### CONSTRUCTION

The FLDL-UL-SG1 or SG2 is a fire rated fusible link door louver constructed of all steel components (see option) with a removable lattice face plate.


#### INSTALLATION

The FLDL-UL-SG1 or SG2 is installed in door (1-3/4" thick) door cutouts by means of self attaching #8 x 1" phillips head screws that fasten the auxiliary frame to the louver core through the door cutout the corridor side of the frame is free of fasteners for added security (tamperproof screws optional). Optional insect screens are available loose or attached.

#### FIRE RATINGS (WITH UL AND W.H.I. LABEL) POSITIVE PRESSURE

- 20/45/60/90 MINUTES: Approved listing (max width 24", max height 24") (min width 12", min height 6")

### FLDL-UL-SG1



For a 3-Dimensional Drawing  
See Table of Contents page E-2

### FLDL-UL-SG2

