MODEL
- ☑ **RME** - Bypass / Relief Terminal

INLET SIZE
- ❑ 5" Ø
- ❑ 6" Ø
- ❑ 7" Ø
- ❑ 8" Ø
- ❑ 9" Ø
- ❑ 10" Ø
- ❑ 12" Ø
- ❑ 12" x 12"
- ❑ 16" x 12"

CASING CONSTRUCTION
- ☑ Galvanized Steel 22 Gauge

CASING TREATMENTS
- ❑ 1/2" Matte Insulation
- ❑ 1" Matte Insulation
- ❑ 1/2" Foil Faced Insulation
- ❑ 1" Foil Faced Insulation
- ❑ 3/8" Fiber-Less Insulation

CONTROL SYSTEM
- ❑ Pneumatic Controls
- ❑ Electronic Analog Controls
- ❑ Electric Controls

Control strategies available for all applications

CONTROL SIDE
- ❑ Right Side
- ❑ Left Side

REHEAT OPTIONS
- ❑ 1 Row Hot Water Coil
- ❑ 2 Row Hot Water Coil
- ❑ 4 Row Hot Water Coil
- ❑ Electric Coil (Field Installed Downstream of Box)

- ❑ Right Hand Connection
- ❑ Left Hand Connection

ACCESSORIES

CASING OPTIONS
- ❑ Unit Mounting Bracket (shipped loose)
- ❑ Standard Control Enclosure
- ❑ Hinged Front Panel (control enclosure)

ELECTRIC CONTROLS
- ❑ Control Transformer
- ❑ Low Voltage Control Disconnect Switch
- ❑ Low Voltage Fuse & Fuse Block
- ❑ Low Voltage Disconnect Switch
- ❑ Low Voltage Power-Fusing