Models FFS-200 FFR-200

FREE FLO[™]

Architectural Linear Slot Diffusers

Surface Frame / Border

2" Slot Width

SUBMITTAL SHEET


www.anemostat-hvac.com

		2" Slot Wlath
PRODUCT FEATURES	CONSTRUCTION DETAILS	MODELS
Pattern / volume controllers field adjusted for horizontal to vertical air discharge directions	Extruded aluminum, adjustable linear slot diffuser	FFS-200 Supply
Diffuser lengths can be ordered in 1/32" increments	Finish:	FFR-200 Return
Diffuser end caps factory attached & tap onto diffuser ends	Arctic White powder coat outer frames and center tees. Black volume / pattern controllers	(Return model excludes Volume / Pattern Controllers)
Continuous run applications use multiple diffusers using alignment strips in keyways (included if applicable)	Optional Anemostat Color	
•Includes plenum mounting brackets and screws	Custom Color Match	
•See <i>Model AD</i> Air Distribution plenums engineered for use with this diffuser (optional)		
Plenum (optional) D +1/16 Mou Brace	Multiple-Slot (2 Standard Controllers) Multiple-Slot (2 Standard Controllers) Multiple-Slot (2 Standard Controllers) E - Q - Q - T - T - COntrollers	2-5/8
Ceiling Opening Diffuser Length +	1/2	

- •Diffuser Length = Order Size and is actual cut length of linear diffuser (excludes end caps)
- •End caps can be added or removed from the diffuser in the field
- •Model AD Plenum Order Length = Model FFS Order Length

ΑII	dimensions	are	in	inches.

Models	Slot Width	# of Slots	E Ceiling Opening	С	D	Т	Q	F Range
FFS-200 FFR-200	2 3 4	4-3/8	5-1/2	4-5/16	4-1/16	4-11/32	1-25/32 to 2-5/32	
		8-3/8	9-1/2	8-5/16	8-1/16	8-11/32		
		12-3/8	13-1/2	12-5/16	12-1/16	12-11/32		
		4	16-3/8	17-1/2	16-5/16	16-1/16	16-11/32	



Recommended Hem Detail (Duct must be hemmed to use mounting brackets)

DWG #: FF-S-0330

JOB NAME:

SUBMITTED BY:

- - 1-1/8