Models FFS-300 FFR-300

FREE FLO[™]

Architectural Linear Slot Diffusers

Surface Frame / Border

3" Slot Width

SUBMITTAL SHEET

www.anemostat-hvac.com

FFR-300

JOB NAME:

2

12-3/8

PRODUCT FEATURES				CON	CONSTRUCTION DETAILS				MODELS		
Pattern / volume controllers field adjusted for horizontal to vertical air discharge directions					• Extruded aluminum, adjustable linear slot				300 St	ipply	
*Diffuser lengths can be ordered in 1/32" increments					diffuser Finish:				FFR-300 Return		
Diffuser end caps factory attached & tap onto diffuser ends					Arctic White powder coat outer frames and center tees. Black volume / pattern controllers				(Return model excludes Volume / Pattern Controllers)		
•Continuous run applications use multiple diffusers using alignment strips in keyways (included if applicable)					Optional Anemostat Color						
•Includes plenum mounting brackets and screws				☐ Cu	Custom Color Match						
•See <i>Model AD</i> Air Distribution plenums engineered for use with this diffuser (optional)											
Model AD Plenum (optional) Alignment Strips		C	6 Bra	Ouct unting ackets Adjusta Volum Patter Control	e / rn 	Multiple	E Q T	Slot Sho	own)	3-7/32	
1/16 →		Dif	eiling Opening fuser Length + Diffuser Length	1/2		End Ca	0				
 Diffuser Length = Order Size and is actual cut length of linear diffuser (excludes end caps) End caps can be added or removed from the diffuser in the field Model AD Plenum Order Length = Model FFS Order Length All dimensions are in inches. 											
Models		of lots	E Ceiling Opening	С	D	Т	Q	F Range	3/8 to 3/4	<u> </u>	
FES-300		1	6-3/8	7	6-5/16	6-3/32	6-3/8	2-2/9+a	Recommen	ded Hem Detail	

12-5/16

12-3/32

SUBMITTED BY:

13

(Duct must be hemmed

to use mounting brackets)

2-3/4

DWG #: FF-S-0332

12-3/8