




PRODUCT FEATURES

- Minimum Panel Size:
12" x 12"
- Maximum Single Panel Size:
40 Sq. Feet Section Size.
Louver larger than the maximum
factory assembled size will require
field assembly of smaller louver
sections.

CONSTRUCTION FEATURES

- Material:**
Extruded Aluminum 6063-T6/T52 Alloy
- .081" (nominal)
- Face of Louver:** Full Width Sill With Head and Blades Contained Within Jambs.
Approximate Blade Centers 5".
- Screen:** (Removable Frame)
- Bird Screen - 1/2" Flattened Aluminum, .051" Thk.
 - 1/2" Sq. Mesh Intermediate Double-Crimped Aluminum Wire, .063" Dia.
 - 18/16 Mesh, .011" Dia. Aluminum Wire Insect Screen.

Finish: _____



All dimensions are in inches.



JOB NAME:

SUBMITTED BY:

PERFORMANCE DATA

EXCELLENT WATER PROTECTION WITH LITTLE PRESSURE LOSS.
TESTS OF A 48"x48" SAMPLE BY AN *AMCA ACCREDITED LABORATORY
ACCORDING TO AMCA STANDARD 500 SHOWS LOW WATER PENETRATION.
TESTS SHOW LESS THAN .01 OZ. PER SQ. FT. WATER PENETRATION AT
1000 FPM (FREE AREA VELOCITY) WITH LESS THAN .19" W.G.
PRESSURE DROP AT 1000 FPM (INTAKE).

RATINGS DO NOT INCLUDE EFFECTS OF BIRDSCREEN.



FREE AREA (SQ. FT.)
WIDTH

	12"	24"	36"	48"	60"	72"	84"	96"	108"	120"
12"	.25	.56	.87	1.19	1.50	1.75	2.06	2.37	2.68	3.00
24"	.74	1.68	2.62	3.55	4.49	5.23	6.17	7.11	8.05	8.98
36"	1.20	2.72	4.24	5.75	7.27	8.47	9.99	11.51	13.03	14.54
48"	1.67	3.79	5.90	8.16	10.12	11.80	13.91	16.02	18.13	20.25
60"	2.15	4.87	7.59	10.31	13.03	15.18	17.90	20.62	23.34	26.06
72"	2.61	5.92	9.22	12.52	15.83	18.44	21.75	25.05	28.35	31.65
84"	3.11	7.04	10.97	14.89	18.82	21.93	25.86	29.79	33.71	37.64
96"	3.57	8.08	12.58	17.09	21.60	25.17	29.68	34.18	38.69	43.20
108"	4.04	9.14	14.25	19.35	24.45	28.49	33.60	38.70	43.80	48.90
120"	4.52	10.23	15.94	21.65	27.36	31.88	37.59	43.30	49.01	54.71



Anemostat certifies that the performance data shown has been determined by test in accordance with applicable AMCA standards.

All dimensions are in inches.

JOB NAME:

SUBMITTED BY: