

CORE PATTERNS (FIELD CONFIGURABLE) DUCT SIZES Note diffuser ships with 4-Way Pattern / Square duct sizes only 16 x 16 18 x 18 20 x 20

2-way 3-way 3-way corner opposite IMPORTANT: It is the specifier's responsibility to properly configure the HVAC system to meet the appropriate level of comfort, safety, security and detention All dimensions are in inches. **PRODUCT FEATURES** Order Size Q **Face Plate Thickness** Finish (NOM DUCT SIZE) Т White Powder Coat (STANDARD) 12 GA. (STANDARD) Υ W н | 10 GA. 14 GA. Rust-Inhibiting Primer Other ____ Other **Perforated Hole Pattern Tamper-Proof Screws** (P2) 13/16" Sq. Holes on 1" Centers (STD) #10 x 1-1/2" Pinned Flat Head Torx Sheet

Metal Screws (STANDARD) (P1) 9/16" Sq. Holes on 11/16" Centers No Screw Holes or Screws / No Rear Frame (P8) 1/4" Dia. Holes on 3/8" Staggered Ctrs Other (P9) 5/16" Dia. Holes on 7/16" Staggered Ctrs **OPTIONAL ACCESSORIES** Other **Face Material** Model OB-1 Opposed Blade Damper - Front Operated, Attached (requires hole drilled in Plain Steel (STANDARD) core for damper access) 304 Stainless Steel* 316 Stainless Steel* Model OB-1 Opposed Blade Damper - (Ships Aluminum* Galvanized* Loose) Other Model SRA Square to Round Duct (ships loose) *(Consult factory for availability)

4-wav

Other Options (please specify)

JOB NAME:

06 x 06

08 x 08

10 x 10

12 x 12

14 x 14

22 x 22

24 x 24

SUBMITTED BY:

Product information is subject to change without notice. Drawing is not to scale.

2-wav

1-way