

MINIMUM SECURITY

STANDARD FEATURES

- FACE PLATE: 12 GA C.R.S., with 9/16" square holes on 1 1/16" centers
- TAMPERPROOF SCREWS: #10 x 1-1/2" Pinned Flat Head TORX

FINISH


- STANDARD: White Powder Coat Finish
- OPTIONAL: Rust Inhibiting Prime Coat. Consult factory for other finishes

OPTIONAL FEATURES

- ASFP - FACE PLATE PATTERNS:
 - 13/16" square holes on 1" centers
 - 1/4" diameter holes on 3/8" staggered centers
 - 5/16" diameter holes on 7/16" staggered centers
- ASFP-RR* ...FACE PLATE: 12 GA C.R.S. perforated face with 3/16" diameter holes on 9/32" staggered centers
- MATERIAL GAUGES: 3/16", 10 GA, 14 GA
- MATERIAL: Stainless Steel, Aluminum, or Galvanized (consult factory for availability)
- TAMPERPROOF SCREWS: See inside back cover, page i, and consult factory for specific product applications
- OPPOSED BLADE DAMPER: front or rear operated, with attached auxiliary frame
- ADAPTER: square to round (shipped loose)

INSTALLATION

The ASFP is installed in the ceiling and secured to the support frame by others. Typical application is for a non-ducted return or exhaust unit. See inside back cover, page i, for Installation Overview.



ASFP-RR *

3/16" DIA. HOLES ON 9/32" STAGGERED CENTERS

- * California Title 24 Compliant for Suicide Resistance
Performance Data available upon request

