

## MEDIUM SECURITY

### STANDARD FEATURES

- FACE FRAME: 16 GA C.R.S.
- ADJUSTABLE LOUVER BARS: specify 0° /40° deflection  
13 GA round edge steel - spaced 1/2" on centers.
- LOUVER SUPPORT BARS: 13 GA round edge steel - spaced on 6" maximum centers
- STEEL WOVEN MESH: 10 GA with 1/2" on 5/8" centers - welded to the frame
- TAMPERPROOF SCREWS: #10 x 1-1/2" Pinned Flat Head TORX

### FINISH

- STANDARD: White Powder Coat
- OPTIONAL: Consult factory for other finishes

### OPTIONAL FEATURES

- MATERIAL GAUGE: face frame - 14 GA
- MATERIAL: Stainless Steel, Aluminum, or Galvanized (consult factory for availability)
- STEEL SLEEVE GAUGE: 16 GA, 18 GA (specify length)
- LOCKING ANGLES: Two pieces 1" x 1" x 3/16" (shipped loose for field installation)
- LOCKING ANGLE FRAME: 1" x 1" x 3/16" welded one piece steel angle (shipped loose for field installation). Other sizes available - consult factory.

NOTE: SCREW HOLES OMITTED WHEN SLEEVE AND LOCKING ANGLES OR LOCKING ANGLE FRAME SPECIFIED

- OPPOSED BLADE DAMPER: front or rear operated
- TAMPERPROOF SCREWS: See inside back cover, page i, and consult factory for specific product applications
- ADAPTER: square to round (shipped loose)

### CONSTRUCTION

The HD15-MS is constructed of all steel components with reinforced welded seams and support bars on 6" centers and backed with steel woven mesh welded to the unit to ensure optimum security.

### INSTALLATION

The HD15-MS can be installed with security screws through the face or installed through the wall. It is secured from the back by the locking angles and welded by others to the sleeve. (The face mounting screw holes are omitted). See inside back cover, page i, for Installation Overview.

