MODELS
- ❑ SCD - SUPPLY
- ❑ SCR - RETURN

CEILING STYLE
- ❑ SURFACE MOUNT (MUST INCLUDE PLASTER FRAME OPTION)
- ❑ LAY-IN
- ❑ 9/16" NARROW SLOT

INSTALLATION TYPE
- ❑ ALL CENTER TEES INCLUDED FOR 2, 3, & 4 SLOT UNITS
- ❑ 2' X 2' CROSSOVER (NOTCH IN CENTER OF 4' PLENUM)
- ❑ STRADDLE (2 SLOT ONLY) NO CENTER TEE. UNIT INCLUDES NOTCHED END CAPS FOR GRID MEMBER
- ❑ COMBINATION CROSSOVER & STRADDLE FEATURE (2 SLOT ONLY)

OF SLOTS
- ❑ 1 SLOT
- ❑ 2 SLOT
- ❑ 3 SLOT
- ❑ 4 SLOT

SLOT WIDTH
- ❑ 3/4" SLOT
- ❑ 1" SLOT
- ❑ 1-1/2" SLOT

NOMINAL LENGTH
24" TO 60" SINGLE PIECE CONSTRUCTION

INLET SIZE
- ❑ 5" Ø
- ❑ 6" Ø
- ❑ 7" Ø
- ❑ 8" Ø
- ❑ 9" Ø
- ❑ 10" Ø
- ❑ 12" Ø

INSULATION TYPE
- ❑ NO INSULATION
- ❑ INTERNAL INSULATION
- ❑ EXTERNAL FOIL INSULATION
- ❑ INTERNAL FOIL INSULATION
- ❑ CLOSED CELL FIBER FREE INSULATION

FIRE STOP DAMPER
- ❑ NONE
- ❑ FIRE STOP DAMPER

SIDE T-BARS & CLIPS
- ❑ NONE
- ❑ 1 T-BAR ONE SIDE ONLY*
- ❑ 2 T-BARS BOTH SIDES
- ❑ 1 T-BAR W/ CLIPS ONE SIDE*
- ❑ CLIPS BOTH SIDES

* SPECIFY LOCATION INLET SIDE OR BACK SIDE

* WHITE T-BARS ARE STANDARD

PLASTER FRAME
(SURFACE APPLICATION ONLY)
- ❑ NONE
- ❑ T-BAR PLASTER FRAME (WHITE IS STANDARD)

INLET DAMPER
- ❑ NONE
- ❑ ROUND INLET DAMPER
- ❑ ROUND INLET DAMPER W/ CONTROL ROD ATTACHED

FINISH
- ❑ BLACK EXPOSED INTERIORS & LOWER FLANGES
- ❑ WHITE EXPOSED INTERIORS & LOWER FLANGES

(2 Slot Shown)